

## HY-226M/HY-256M

### 3 tones electronic buzzer

- Compact, light weight and composed of 3 melodies
- Front LED lighted when operating the buzzer
- Excellent attachment due to the panel type
- Low power consumption



#### ●● Suffix code

Model	Code	Description
HY-	<input type="checkbox"/> <input type="checkbox"/>	3 tones electronic buzzer
Dimension	226	Ø22 / Ø25 dual usage (Rectangular shaped front)
	256	For Ø25 installation (Round shaped front)
Power supply voltage	MD	12 – 24 V d.c
	MA	100 – 240 V a.c

#### ●● Specification

Model	HY-226MD	HY-226MA	HY-256MD	HY-226MA
Installation diameter	Ø22 / Ø25 dual usage		Ø25	
Power supply voltage	12 – 24 V d.c	100 – 240 V a.c (50 – 60 Hz)	12 – 24 V d.c	100 – 240 V a.c (50 – 60 Hz)
Power consumption	0.6 W	13.5 W	0.6 W	13.5 W
Volume	80 dB	80 dB	80 dB	80 dB

#### ●● Tone selection

Tone selection	Tone symbol	Information
SELECT-1	🔊.....	fast beeping
SELECT-2	🔊-----	slow beeping
REMOVE	🔊————	Continuous tone

●● Dimension (unit : mm)

Model	Appearance	Dimension	
HY-226			
HY-256			

Control switch  
Combination display light


Power switch  
Main switch  
Cam switch

Limit switch  
Micro switch


Hoist switch  
Foot switch  
Mono lever switch

●● Panel cutout dimension (unit : mm)

• HY-226



• HY-226 / HY-256



Sign tower  
Signal light

Buzzer  
Terminal block  
Fuse holder

Control box  
Cable connector

Discontinued Products